



Machinery Parts Co., Ltd.

5SRS9XGM[SS,SSHH,UU]C1+[32-1000/1]
L[H,P]M THK Miniature Linear Guide Full Ball
SRS-G Accuracy and Preload Selectable

Bearing No.
5SRS9XGM[SS,SSHH,UU]C1+[32-1000/1]L[H,P]M

5SRS9XGM[SS,SSHH,UU]C1+[32-1000/1]L[H,
P]M Bearing 2D drawings and 3D CAD models

Days to Ship	3 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	5
Nominal Part Number	9
Rail Type	Standard
Rail Width W1	9 mm
Mounting Height M	10 mm
Rail Length L	32 ~ 1000 mm
Radial Clearance	Light Preload
Accuracy Grade	High Grade / Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	2220
Basic Load Rating Static Rating Co(N)	3060
Allowable Static Moment MA(N m)	9.87
Allowable Static Moment MB(N m)	11.4
Allowable Static Moment MC(N m)	14.1
Symbols for Dust Resistance	UU: End Seals
Advanced Seal Options (Longer Leadtime)	SSHH: SS + Laminated Contact Scraper LaCS



Machinery Parts Co., Ltd.

Block external dimension W	20 mm
Block external dimension L	30.8 mm
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	2.8 mm
Block dimension L1	19.8 mm