



Machinery Parts Co., Ltd.

5SRS12WS[SS,SSHH,UU]+[61-900/1]LM THK Miniature Linear Guide Caged Ball SRS Series

Bearing No. 5SRS12WS[SS,SSHH,UU]+[61-900/1]LM

5SRS12WS[SS,SSHH,UU]+[61-900/1]LM Bearing
2D drawings and 3D CAD models

Days to Ship	22 Days
Block Type	[Short] S: Short
The number of LM blocks combined with a axis	5
Nominal Part Number	12W
Rail Type	Wide Rail
Rail Width W1	24 mm
Mounting Height M	14 mm
Rail Length L	61 ~ 900 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	3580
Basic Load Rating Static Rating Co(N)	3150
Allowable Static Moment MA(N m)	9.77
Allowable Static Moment MB(N m)	9.77
Allowable Static Moment MC(N m)	39.5
Symbols for Dust Resistance	SS: End and Side Seals / UU: End Seals (Best Leadtime)
Advanced Seal Options (Longer Leadtime)	SSHH: SS + Laminated Contact Scraper LaCS



Machinery Parts Co., Ltd.

Block external dimension W	40 mm
Block external dimension L	30.5 mm
Number of Block Mounting Holes(holes)	2
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	3.5 mm
Block dimension L1	16.9 mm