



Machinery Parts Co., Ltd.

HSR65HB[1,2,3,4,5,6,7,8,9]+ [263-3000/1]L THK Standard Linear Guide Accuracy and Preload Selectable HSR Series

Bearing No.
HSR65HB[1,2,3,4,5,6,7,8,9]+[263-3000/1]L

HSR65HB[1,2,3,4,5,6,7,8,9]+[263-3000/1]L Bearing 2D drawings and 3D CAD models

Days to Ship	42 Days
Block Type	[Wide Long] HB: Long Flanged w/Thru Holes
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	65
Rail Width W1	63 mm
Material	Carbon Steel
Mounting Height M	90 mm
Rail Length L	263 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Retainer	Available
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	249000
Basic Load Rating Static Rating Co(N)	323000
Allowable Static Moment MA(N m)	9810
Allowable Static Moment MB(N m)	9810
Allowable Static Moment MC(N m)	8790
Block external dimension	170 mm



Machinery Parts Co., Ltd.

W	
Block external dimension L	245.5 mm
Mounting hole for blocks	Thru Holes
Number of Block Mounting Holes(holes)	6
Mounting Hole Dimension H(\varnothing)	16
Mounting Hole Screw Depth	Through mm
Block dimension L1	206.5 mm