



Machinery Parts Co., Ltd.

5SRS12GN+[61-900/1]L[H,P]M THK Miniature Linear Guide Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. 5SRS12GN+[61-900/1]L[H,P]M

5SRS12GN+[61-900/1]L[H,P]M
drawings and 3D CAD models

Bearing 2D

Days to Ship	22 Days
Block Type	[Long] N: Long
The number of LM blocks combined with a axis	5
Nominal Part Number	12
Rail Type	Standard
Rail Width W1	12 mm
Mounting Height M	13 mm
Rail Length L	61 ~ 900 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	4720
Basic Load Rating Static Rating Co(N)	6830
Allowable Static Moment MA(N m)	34.8
Allowable Static Moment MB(N m)	34.8
Allowable Static Moment MC(N m)	44.7
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	27 mm
Block external dimension L	47.1 mm



Machinery Parts Co., Ltd.

Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	3.2 mm
Block dimension L1	33.3 mm