



Machinery Parts Co., Ltd.

5SRS25M+[78-900/1]L[H,P]M THK Miniature Linear Guide Caged Ball SRS Series

Bearing No. 5SRS25M+[78-900/1]L[H,P]M

Days to Ship	22 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	5
Nominal Part Number	25
Rail Type	Standard
Rail Width W1	23 mm
Mounting Height M	25 mm
Rail Length L	78 ~ 900 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	16500
Basic Load Rating Static Rating Co(N)	20200
Allowable Static Moment MA(N m)	177
Allowable Static Moment MB(N m)	177
Allowable Static Moment MC(N m)	248
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	48 mm
Block external dimension L	77 mm
Number of Block Mounting	4

5SRS25M+[78-900/1]L[H,P]M Bearing 2D drawings and 3D CAD models



Machinery Parts Co., Ltd.

Holes(holes)	
Mounting Hole Dimension S(M)	M6
Mounting Hole Screw Depth	7 mm
Block dimension L1	56 mm