



# Machinery Parts Co., Ltd.

## HSR85B[1,2,3,4,5,6,7,8,9]+[2 63-3000/1]L THK Standard Linear Guide Accuracy and Preload Selectable HSR Series

Bearing No.  
HSR85B[1,2,3,4,5,6,7,8,9]+[263-3000/1]L

HSR85B[1,2,3,4,5,6,7,8,9]+[263-30  
00/1]L Bearing 2D drawings and 3D CAD models

Days to Ship	32 Days
Block Type	[Wide] B: Flanged w/Thru Holes (Obsolete)
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	85
Rail Width W1	85 mm
Material	Carbon Steel
Mounting Height M	110 mm
Rail Length L	263 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Retainer	N/A
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	304000
Basic Load Rating Static Rating Co(N)	355000
Allowable Static Moment MA(N m)	10200
Allowable Static Moment MB(N m)	10200
Allowable Static Moment MC(N m)	12800
Block Mounting Hole Pitch	185 mm



## Machinery Parts Co., Ltd.

(Width Direction)	
Block Mounting Hole Pitch (Length Direction)	140 mm
Block Mounting Hole Diameter	18
Rail Mounting Hole Pitch	180 mm
Rail Mounting Hole Diameter	24
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	215 mm
Block external dimension L	245.6 mm
Mounting hole for blocks	Thru Holes
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension H( $\varnothing$ )	18
Mounting Hole Screw Depth	Through mm
Block dimension L1	178.6 mm