



Machinery Parts Co., Ltd.

5SRS15WGM+[57-1000/1]LM THK Miniature Linear Guide Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. 5SRS15WGM+[57-1000/1]LM

5SRS15WGM+[57-1000/1]LM Bearing 2D drawings and 3D CAD models

Days to Ship	3 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	5
Nominal Part Number	15W
Rail Type	Wide Rail
Rail Width W1	42 mm
Mounting Height M	16 mm
Rail Length L	57 ~ 1000 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	7430
Basic Load Rating Static Rating Co(N)	8590
Allowable Static Moment MA(N m)	52.7
Allowable Static Moment MB(N m)	52.7
Allowable Static Moment MC(N m)	178
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	60 mm
Block external dimension L	55.5 mm



Machinery Parts Co., Ltd.

Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M4
Mounting Hole Screw Depth	4.5 mm
Block dimension L1	38.9 mm