



Machinery Parts Co., Ltd.

HSR100HA[1,2,3,4,5,6,7,8,9]
 [RR,SS,UU]C[0,1]+[351-3000/1]L THK
 Standard Linear Guide Accuracy and Preload
 Selectable HSR Series

Bearing No.
 HSR100HA[1,2,3,4,5,6,7,8,9][RR,SS,UU]C[0,1]+[351-3000/1]L

HSR100HA[1,2,3,4,5,6,7,8,9][RR,SS,UU]C[0,1]+[351-3000/1]L Bearing 2D drawings and 3D CAD models

Days to Ship	32 Days
Block Type	[Wide Long] HA: Long Flanged w/Tapped Holes
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	100
Rail Width W1	100 mm
Material	Carbon Steel
Mounting Height M	120 mm
Rail Length L	351 ~ 3000 mm
Radial Clearance	Light Preload / Medium Preload
Accuracy Grade	Normal Grade (Best Leadtime)
Retainer	N/A
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	441000
Basic Load Rating Static Rating Co(N)	540000
Allowable Static Moment MA(N m)	20700
Allowable Static Moment MB(N m)	20700



Machinery Parts Co., Ltd.

Allowable Static Moment MC(N m)	24100
Block Mounting Hole Pitch (Width Direction)	220 mm
Block Mounting Hole Pitch (Length Direction)	200 mm
Block Mounting Hole Diameter	18
Rail Mounting Hole Pitch	210 mm
Rail Mounting Hole Diameter	26
Symbols for Dust Resistance	SS: End and Side Seals (Best Leadtime) / UU: End Seals
Advanced Seal Options (Longer Leadtime)	RR: Low Resistance End + Side Seal
Block external dimension W	250 mm
Block external dimension L	334 mm
Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	9
Mounting Hole Dimension S(M)	M18
Mounting Hole Screw Depth	Through mm
Block dimension L1	261 mm