



Machinery Parts Co., Ltd.

6SRS7GS[SS,UU]+[33-300/1]LM THK Miniature Linear Guide Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. 6SRS7GS[SS,UU]+[33-300/1]LM

6SRS7GS[SS,UU]+[33-300/1]LM
drawings and 3D CAD models

Bearing 2D

Days to Ship	27 Days
Block Type	[Short] S: Short
The number of LM blocks combined with a axis	6
Nominal Part Number	7
Rail Type	Standard
Rail Width W1	7 mm
Mounting Height M	8 mm
Rail Length L	33 ~ 300 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	946
Basic Load Rating Static Rating Co(N)	1160
Allowable Static Moment MA(N m)	1.96
Allowable Static Moment MB(N m)	2.25
Allowable Static Moment MC(N m)	4.49
Symbols for Dust Resistance	UU: End Seals
Block external dimension W	17 mm
Block external dimension L	19 mm



Machinery Parts Co., Ltd.

Number of Block Mounting Holes(holes)	2
Mounting Hole Dimension S(M)	M2
Mounting Hole Screw Depth	2.3 mm
Block dimension L1	9 mm