



Machinery Parts Co., Ltd.

8HR2555TM[F(AP-C),F(AP-CF),F(AP-HC)]+[148-1000/1]L[H,P,SP,UP]M THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 8HR2555TM[F(AP-C),F(AP-CF),F(AP-HC)]+[148-1000/1]L[H,P,SP,UP]M

8HR2555TM[F(AP-C),F(AP-CF),F(AP-HC)]+[148-1000/1]L[H,P,SP,UP]M Bearing 2D drawings and 3D CAD models

Days to Ship	42 Days
Rail Width W1	22 mm
Mounting Height M	25 mm
Number of blocks	8
Material	Stainless Steel
Rail Length L	148 ~ 1000 mm
Accuracy Grade	High Grade / Precision Grade / High Precision Grade / Extra High Precision Grade
Callout Size	2555
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	25100
Basic Load Rating Static Rating Co(N)	40800
Allowable static moment MA(N · m)	1330
Allowable static moment MB(N · m)	1330
The outside dimension W of block	33.3 mm
The outside dimension L of block	146.4 mm
Mounting Hole Dimension S(M)	M8
The dimension L1 of blocks	105.4 mm



Machinery Parts Co., Ltd.

LM Block Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Industrial Black Chrome Coating / Industrial Black Chrome Film Treated - Special Fluororesin Coating / Industrial Hard Chrome Plating
LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Not Provided